



NXTZ with options

## NXTZ Technical Data

Weight	395 kg
Voltage	230 V Mono / 230 V - 3 Phase
	400 V - 3 Phase
Dust suction outlet	100 mm
	+ 60 mm on saw guard

### Saw

Saw rotation speed	4500 RPM
Max. diameter saw blade	315 x 30 mm / 250 x 30 mm when scoring blade is mounted
Scoring unit (option)	100 x 20 mm
Cutting depth at 45°/90° with 250 mm blade	50 mm / 75 mm
Cutting depth at 45°/90° with 315 mm blade	70 mm / 107 mm
Dimensions cast iron table	1150 x 405 mm
Dimensions sliding table	1450 mm (option 2050 mm) x 320 mm
Cutting length	1600 mm (option 2500 mm)
Cutting width parallel fence	700 mm (option 1200 mm)
Motor power 3 phase (S6)	3,72 kW / 5 hp
Motor power single phase (S6)	2,2 kW / 3 hp

### Spindle

Spindle rotation speed machine 400 V	3000 / 6000 / 7500 / 10000 RPM
Spindle rotation speed single phase	3000 / 6000 / 7500 / 10000 RPM
Diameter spindle arbor	30 mm (option 50mm)
Capacity spindle arbor	120 mm
Travel	140 mm
Dimensions table opening	180 mm
Motor power 3 phase (S6)	3,72 kW / 5 hp
Motor power single phase (S6)	2,2 kW / 3 hp

